



## BUTTERFLY VALVE



SL NO	FEATURES	RANGE													
1.	PRODUCT	BUTTERFLY VALVE													
2.	TYPE	CENTER DISC / DOUBLE OFFSET													
3.	SIZE (in mm)	40	50	65	80	100	150	200	250	300	350	400			
4.	CLASS	PN2.5			PN6		PN10		PN16		#150		#300		
5.	ENDS	WAFER END			LUGGED END			DOUBLE FLANGED							
6.	OPTIONAL FEATURES	METAL SEATED				EXTENDED BONNET				LOCKING ARRANGEMENT					
7.	OPERATION	LEVER			GEAR			PNEUMATIC			ELECTRICAL				
8.	DESIGN STD	BS 1868 / API 602													
9.	FACE TO FACE	API 609 / IS 13095 / EN 558													
10.	FLANGE DRILLING	ASME B16.5													
11.	TESTING STD	API 598 / BS EN 12266													
12.	SHELL MATERIAL	WCB	CF8	CF8M	CF3	CF3M	CN7M	CI	DI						
13.	TRIM MATERIAL	410	304	316	304L	316L									
14.	SEAT MATERIAL	EPDM			NBR		PTFE			304+STL		316+STL			
NOTE: OTHER FEATURES ARE ALSO AVAILABLE ON CUSTOMERS REQUEST.															