




<b>GLOBE VALVE</b>																
SL NO	FEATURES	RANGE														
1.	PRODUCT	GLOBE VALVE														
2.	TYPE	OUTSIDE STEM & YOKE (OS & Y)														
3.	SIZE (in mm)	15	20	25	32	40	50	65	80	100	150	200	250			
4.	CLASS	150			300			600								
5.	ENDS	FLANGED				BUTT WELD										
6.	OPTIONAL FEATURES	METAL SEATED				EXTENDED BONNET				LOCKING ARRNGEMENT						
7.	OPERATION	HAND WHEEL				GEAR				PNEUMATIC			ELECTRICAL			
8.	DESIGN STD	ASME B 16.34 / BS 1873														
9.	FACE TO FACE	ASME B16.10														
10.	FLANGE DRILLING	ASME B16.5														
11.	TESTING STD	BS 1873														
12.	SHELL MATERIAL	WCB	CF8	CF8M	CF3	CF3M	CN7M									
13.	TRIM MATERIAL	CA15	CF8	CF8M	CF3	CF3M	CN7M	304	316	410	17-4PH					
14.	SEAT MATERIAL	410-Hard Face			304-Stellite			316-Stellite								
NOTE: OTHER FEATURES ARE ALSO AVAILABLE ON CUSTOMERS REQUEST.																